SAVANNAH HAYES

PAINTED IN PITTSBURGH · PRINTED IN THE USA

Type II

Type II commercial wallcovering, printed to order.

THE MATERIAL

Type
Type II Commercial Wallcovering
WA-101

Weight
20 oz per Linear Yard
13 oz/sq yd · 457 g/m2

Thickness
0.017" to 0.027"
0.432 to 0.686 mm

Construction
Matte Non-Woven Vinyl
Commercial matte finish face

Selvedge
None
Trimmed directly to edge

Fire Rating
Class A
ASTM E-84 Tunnel Test

Specification
Federal Spec CCC-W-408D
NFPA Life Safety Code 101

CERTIFIED

Sustainability
NSF/ANSI 342 Silver
Contributes to LEED v4

Emissions
CDPH Method 01350
Schools and offices

Composition
Phthalate Free
Prop 65 compliant

Mould
ASTM G-21
Passed all requirements

Maintenance
Washable and Scrubbable
Mild soap and water

Warranty
5 Years
Manufacturing defects

ORDERING

Width
50" Usable
51" printed · 1" bleed, right side

Substrate Roll
54"

Sold By
Linear Yard
15 yard minimum

Lead Time
6 to 8 Weeks
Made to order

Sample
8" x 10"
Printed to order, one to two weeks

Origin
Painted in Pittsburgh
Printed in the USA

INSTALLATION

Prime with a white-pigmented, mildew-inhibiting wallcovering primer. Hang with a heavy-duty clear pre-mixed adhesive containing a mildew inhibitor; paste the full back and book for ten minutes. Tape the seams, then overlap and double cut. Reverse-hang alternate panels on non-matched patterns and allow four inches over the wall height. Install and store above 65°F. For interior use in environmentally controlled spaces. Full instructions available on request.

Every property above is the certified specification of the DreamScape 20 oz Type II substrate.